PRO32 MEDIUM ACTIVATOR

Page: 1

Compilation date: 16/10/2012

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PRO32 MEDIUM ACTIVATOR

Product code: PRO32-8.5, PRO32-Q

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: HARDENER CONTAINS ISOCYANATE, XYLENE, MIXTURE OF SOLVENTS

1.3. Details of the supplier of the safety data sheet

Company name: Pro Line Performance Products

PO Box 1136 Olympia WA 98507 USA

Website: ProLinePerformanceProducts.com

1.4. Emergency telephone number

Emergency tel: 1-800-424-9300 (CHEMTREC)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R10; Xn: R20/21; Xi: R37/38; Sens.: R43

Most important adverse effects: Flammable. Harmful by inhalation and in contact with skin. Irritating to respiratory

system and skin. May cause sensitisation by skin contact.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Harmful.



Risk phrases: R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R37/38: Irritating to respiratory system and skin.

R43: May cause sensitisation by skin contact.

Safety phrases: S24: Avoid contact with skin.

S23: Do not breathe fumes.

S36/37: Wear suitable protective clothing and gloves.

S42: During fumigation / spraying wear suitable respiratory equipment.

PRO32 MEDIUM ACTIVATOR

Page: 2

Precautionary phrases: Contains isocyanates. See information supplied by the manufacturer.

2.3. Other hazards

Other hazards: May cause sensitisation by skin contact.

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HEXAMETHYLENE DIISOCYANATE OLIGOMERS

EINECS	CAS	CHIP Classification	CLP Classification	Percent
500-060-2	28182-81-2	Xn: R20; Xi: R37; Sens.: R43	-	30-40%
XYLENE				
215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	-	20-30%
N-BUTYL ACE	TATE			
204-658-1	123-86-4	-: R10; -: R66; -: R67 Substance with a Community workplace exposure limit.	-	12.5- 20%
2-METHOXY-1	I-METHYLETHY	L ACETATE		
203-603-9	108-65-6	-: R10 Substance with a Community workplace exposure limit.	-	12.5- 20%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and

footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

 $\label{logistion:logistical} \textbf{Ingestion:} \ \ \textbf{There may be soreness and redness of the mouth and throat.}$

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

PRO32 MEDIUM ACTIVATOR

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Do not use water.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container

tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

PRO32 MEDIUM ACTIVATOR

Page: 4

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m3	0.07 mg/m3	-	-

Hazardous ingredients:

HEXAMETHYLENE DIISOCYANATE OLIGOMERS

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 - 0.07 mg/m3		-	-
WW ENE				

XYLENE

UK 220	mg/m3 441 mg/m3	-	-
--------	-----------------	---	---

N-BUTYL ACETATE

UK	724 mg/m3	966 mg/m3	-	-

2-METHOXY-1-METHYLETHYL ACETATE

OR 27 + mg/mo 0+0 mg/mo	UK	274 mg/m3	548 mg/m3	-	
-----------------------------	----	-----------	-----------	---	--

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Compressed airline breathing apparatus (EN139).

Hand protection: Nitrile gloves.Eye protection: Face-shield.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Aromatic

Evaporation rate: Moderate
Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: 100 cps

Flammability limits %: lower: 1.0 upper: 6.6

Flash point°C: 24 Autoflammability°C: 490

Relative density: 1.0 VOC g/l: 585 (4.92 lb/gal)

PRO32 MEDIUM ACTIVATOR

Page: 5

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Acids. Bases. Oxidising agents. Amines.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Irritation	INH DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

PRO32 MEDIUM ACTIVATOR

Page: 6

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Very toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Incineration on land.

Recovery operations: Use principally as a fuel or other means to generate energy.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

PRO32 MEDIUM ACTIVATOR

Page: 7

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

Phrases used in s.2 and 3: R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R20: Harmful by inhalation.

R37/38: Irritating to respiratory system and skin.

R37: Irritating to respiratory system.

R38: Irritating to skin.

R43: May cause sensitisation by skin contact.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.